



FOTON

AUMARK



AUMARK
3-150-MT

	AUMARK 3-150-MT
Drive Style	4x2
Steering Wheel Position	Right Hand
MASS	
Manufacturer's Gross Vehicle Mass (GVM)	6,900kg
Manufacturer's Gross Combination Mass (GCM)	8,000kg
Manufacturer's Front Axle Mass (GA Front)	2,500kg
Manufacturer's Rear Axle Mass (GAU Rear)	4,500kg
Permissible Gross Vehicle Mass (V)	6,900kg
Permissible Gross Combination Mass (D/T)	8,000kg
Permissible Front Axle Mass (A Front)	2,500kg
Permissible Rear Axle Mass (A Rear)	4,500kg
Unladen Front Axle Mass (T Front)	1,540kg
Unladen Rear Axle Mass (T Rear)	780kg
Unladen Mass Total (Tare)	2,320kg
DIMENSIONS	
Overall Length (OL)	5,945mm
Overall Width (OW)	2,136mm
Overall Height (OH)	2,180mm
Front Overhang (FOH)	1,095mm
Rear Overhang (ROH)	1,420mm
Wheelbase (WB)	3,360mm
Cab to End of Chassis (CE)	4,205mm
Cab to Rear Axle (CA)	2,785mm
Turning Radius (TR)	6.75m
Fuel Tank Capacity (FTC)	80 litres
PERFORMANCE	
Maximum Speed	108km/h
Gradeability at V	30%
ENGINE	
Make	CUMMINS
Model	ISF2.8s3148T
Max Power- Kw@R/Min	110/3200
Max Power-HP @ R/Min	150/3200
Max Torque-N.M @ R/Min	360/1800-2700
Cylinder	4
Capacity	2.78

TRANSMISSION	
Make	Foton Light Transmission
Model	5S368
Type	5 Speed Manual
Forward Ratios	5.762, 2.922, 1.638, 1, 0.782
Reverse Ratio	5.149
CLUTCH	
Diameter	308mm
Type	Single Plate
Operation	Diaphragm Spring
AXLE	
Front Axle	Whole 1 Type
Rear Axle	Punched and Welded Single-Stage Reduction Drive Axle
Rear Axle Ratio	4.875
SUSPENSION	
Front	Leaf Spring
Rear	Leaf Spring
BRAKES	
System Type	Full Air - Dual Circuit
Emergency	Spring Potential Brake
Auxiliary	Exhaust Brake
ABS	Yes
CAB	
Cab Control	Forward Tilt Cab
No. of Seats	3
ELECTRICAL SYSTEM	
System Voltage	24V
No. of Batteries	2 x 24V
TYRE	
Tyre Size	7R16-14PR
Type	Radial
WARRANTY	
Warranty	2 Year / Unlimited Mileage